



SPÄNNVIDDSTABELL

Spännviddstabell Svenska Takelement:

Bet: Tillåten spännvidd vid Snözoner i meter som uppfyller $L/200$

| | 1,0 | 1,5 | 2,0 | 2,5 | 3,0 | 3,5 |
|-------|-------|-------|-------|-------|-------|-------|
| STE20 | 11,6m | 10,6m | 9,5m | 8,9m | 8,1m | 7,8m |
| STE22 | 12,4m | 11,3m | 10,2m | 9,6m | 8,8m | 8,4m |
| STE26 | 13,5m | 12,3m | 11,2m | 10,5m | 9,5m | 9,0m |
| STE30 | 14,5m | 13,5m | 12,0m | 11,5m | 10,5m | 9,9m |
| STE36 | 16,5m | 15,0m | 13,5m | 13,0m | 12,0m | 11,4m |
| STE40 | 17,5m | 16,3m | 14,7m | 14,0m | 12,9m | 12,3m |
| STE45 | 19,0m | 17,5m | 16,0m | 15,0m | 14,0m | 13,0m |
| STE50 | 20,4m | 19,0m | 17,3m | 16,3m | 15,0m | 14,3m |
| STE60 | 23,0m | 21,0m | 19,5m | 18,5m | 17,0m | 16,5m |

Nedböjningsberäkning enligt Eurokod 5.



E-MAIL



FACEBOOK



TELEFON



LINKEDIN